

## HTD-2003AHD24



- 1/3" 1.3Megapixel, 960P
- Sony CMOS Sensor
- 0.02Lux at F1.2(Sens-up x30)
- 3.6mm Fixed Lens (ICR Type)
- Digital Noise Reduction
- ICR Filter Change Function
- 24EA, 15m IR LED

## HTD-2212AHD



- Sony CMOS Sensor
- 1/3" 1.3Megapixel, 960P
- Sony CMOS Sensor
- 0.02Lux at F1.2(Sens-up x30)
- 2.8~11mm DC Auto Iris Varifocal Lens (ICR Type)
- OSD, AGC, BLC, D-WDR, HLC, AWB, 3DNR, Defog
- ICR Filter Change Function
- 24EA, 15m IR LED

## HTB-5307AHD48



- 1/3" 1.3Megapixel, 960P
- Sony CMOS Sensor
- 0.02Lux at F1.2(Sens-up x30)
- 3.6mm Fixed Lens (ICR Type)
- Digital Noise Reduction
- ICR Filter Change Function
- IP66
- 48EA, 30m IR LED

## HTB-5711AHD



- 1/3" 1.3Megapixel, 960P
- Sony CMOS Sensor
- 0.02Lux at F1.2(Sens-up x30)
- 2.8~11mm DC Auto Iris Varifocal Lens (ICR Type)
- OSD, AGC, BLC, D-WDR, HLC, AWB, 3DNR, Defog
- ICR Filter Change Function
- IP66
- 42EA, 25m IR LED

## HTH-8004AHD



- 1/3" 1.3Megapixel, 960P
- Sony CMOS Sensor
- 0.02Lux at F1.2(Sens-up x30)
- 4mm Fixed Lens (ICR Type)
- OSD, AGC, BLC, D-WDR, HLC, AWB, 3DNR, Defog
- ICR Filter Change Function
- IP66
- Ultra LED: 2 EA, Normal: 60 EA

## HTH-8012AHD



- 1/3" 1.3Megapixel, 960P
- Sony CMOS Sensor
- 0.02Lux at F1.2(Sens-up x30)
- 2.8~12mm DC Iris Megapixel Lens (ICR)
- OSD, AGC, BLC, D-WDR, HLC, AWB, 3DNR, Defog
- ICR Filter Change Function
- IP66
- Ultra LED: 2 EA, Normal: 60 EA



2HDD (or 1HDD & 1e-SATA)

Digital Zoom

DDNS, DHCP, UPnP

Multi-Language Supported

Privacy Zone

Covert Channel

Two-way Audio

RAID1 (Optional)

End of Line Resistor Sensor

Dual 485 Port

Coaxitron

Certification : CE, FCC, RoHS compliance

Various Network Software : VMS, RMS, Web Viewer, Mac Viewer

Smartphone Viewer Support : Android/iPhone/iPad

Camera Tamper Sensor

POS/ATM

iSCSI (Recording)

OS : Embedded Linux

Compression : G.711U

Power Supply : 12V/5A-Level 5

Consumption : 60Watts

Operating Temp : 5~40°C

Humidity : 10~80%

Net Weight (W/O HDD) : 3kg

Equalizer